

RUBBER HOSE ASSEMBLIES

HIGH QUALITY, AMERICAN MADE RUBBER AIR BRAKE HOSES

- Minimum Burst Pressure of **900 PSI**
- Conforms to **SAE J1402** and **DOT-106** Specifications
- Maximum Operating Pressure of **225 PSI**
- Operating Temperature of **-40°F to +212°F**
- Resistant to Gasoline, Diesel Fuel, Oil, and Commonly Used Road and Cleaning Chemicals
- Perforated Hose Cover Allows Moisture to Escape from the Reinforcement Layer



BEST

PERMANENT SWIVEL HOSE ASSEMBLIES

- Made of All-Brass Swivel Fittings
- Permanent (also known as Live) Swivel Fittings Retain Swivel Ability After Installation
- Available in **1/2" or 3/8" I.D. Hose** with double swivel 3/8"-18 NPTF fittings
- Available in **3/8" I.D. Hose** with double swivel 1/4"-18 NPTF fittings



BETTER

MAXXDUTY™ HOSE ASSEMBLIES

- New Plating Specifically Engineered to Fight Corrosion
- Originally Developed for Naval Applications Where Parts are Continuously Exposed to Salt Spray
- Retains Rust Free Finish Longer than Industry Standard Hose Assemblies
- Retains Swiveling Ability Even After Long-Term Exposure to Corrosive Chemicals
- Available in **3/8" I.D. Hose** with 1/4"-18 and 3/8"-18 fittings. One fixed & one swivel fitting or with two swivels
- Available in **1/2" I.D. Hose** with 3/8"-18 and 1/2"-14 fittings. One fixed & one swivel fitting or with two swivels



GOOD

RUBBER AIR BRAKE HOSE ASSEMBLIES

- Available in **3/8" I.D. Hose** with 1/4"-18 and 3/8"-18 fittings. One fixed & one swivel fitting or with two swivels
- Available in **1/2" I.D. Hose** with 3/8"-18 and 1/2"-14 fittings. One fixed & one swivel fitting or with two swivels

USED BY MOST MAJOR TRAILER MANUFACTURERS!

Tramec Sloan rubber air brake hoses are made in the USA from American-made rubber hose and brass fittings manufactured by American workers at our plant in Galion, OH which are then assembled in our Holland, MI facility.

At Tramec Sloan, we use the highest quality materials with state of the art, computer driven crimping machines that measure and ensure every hose is assembled correctly every time. With hourly quality checks including pull out, burst and ID flow tests, we make your safety our first priority.

RUBBER HOSE ASSEMBLIES

Available with Springs, Presealed Pipe Threads & Custom Lengths!

ALTERNATIVE PERMANENT SWIVEL

- Innovative, lightweight adapter features the benefits of a light steel collar and cost advantages of reduced material content.
- Seals with an internal O-ring
- Springs not available on 5-Series Swivel Ends



SLIDER (BULKHEAD) HOSE ASSEMBLIES

- Bulkhead Fittings enable quick connection to air brake tubing
- Available in 1/4", 3/8", and 1/2" hose
- Reduces number of fittings needed for application
- Standard grip length is .305, longer length of .55 is available; Consult factory
- Length is measured from hex to hex



COMPOSITE HOSE ASSEMBLIES

- Heavy-Duty Composite Shells with Swivel Fittings
- Meets DOT 106 and SAE J1402



45° FEMALE FLARE HOSE ASSEMBLIES

- Hose meets SAE J1402, DOT FMVSS 106
- Increasingly common newer model trucks and heavy duty equipment.
- Various adapter ends, standard 45° flare connectors.



TRANSMISSION AIR SHIFT ASSEMBLIES

- 1/4" hose with one fixed and one swivel 1/8"-27 NPTF fitting



Tramec Sloan, LLC.
TRAMECSLOAN.COM
P: 800.336.7778
F: 877.286.6515

LIT-FS-24 | V. 022317

FOLLOW US ON TWITTER! @TRAMECSLOAN